



SR STILE & RAIL DOOR COMPONENTS

Ready to machine components for interior stile and rail door constructions. LSL-cored stiles designed for straightness, machining consistency, and superior fastener holding—built to perform better than solid wood alternatives. Our pre-engineered, ready-to-machine components eliminate secondary milling, reduce material handling, and help stabilize production schedules.

WHY TIMBERSTRAND® LSL

- Consistent screw, nail, and dowel holding
- No knots, voids, or warp like solid lumber
- Engineered for dimensional stability over time
- Frees up your labor, space, and Inventory so you can focus on the door

AVAILABLE OPTIONS

- Core: TimberStrand® LSL
- Edges: Solid wood
- Faces: MDF or veneer
- Door thicknesses: 1.375", 1.75", 2.25"
- Machining: Ready-to-machine components



Variety of
Sizing



Superior Hold
Strength



Multiple
Species



Ready to
Machine

WHY LEXINGTON?

At Lexington, we're your go-to problem solvers for component manufacturing, regardless of the substrate or composite material. With strong ties to the fenestration industry, our strengths lie in our people, quality, and ability to customize solutions with over 40 years of engineering prowess. Our approach allows you to concentrate on your core competencies while elevating your efficiency and profitability.



Learn more about
our offers & capabilities



(218) 825-8429

Made in USA

Lexingtonmfg.com